


TRD project status


Alex Bercuci for the TRD

39th CBM Collaboration Meeting
GSI
17th May 2022




Overview

- ◆ Milestones of the project
→ *past & future*
- ◆ Gallery of latest results
→ *measurements & simulations*
- ◆ Outlook
→ *towards CBM day 1*



N. Herrmann, CBM Introduction, CBM without Russia; Joint FAIR ECE 16 and ECSG 07 meeting











Last TODO list

TRD Outlook

C. Blume, TRD: outlook and discussion; 38th CBM Collaboration Meeting 27.09- 1.10 2021




-  critical
-  in progress
-  done


Essential steps in next months

-  • Address comments by ECE on TDR-addendum Slide 11
 -  • Start pre-production of five type-5 modules (delayed pad plane) ⇒ Module-FOS Slide 4
 -  • Finalize SPADIC v2.3 evaluation (v2.3b still to be delivered) ⇒ PRR for v2.4 Slide 8
 -  • Decision on z-layer-spacing in support structure (⇒ radiator design)
 -  • Construction of test gas system (single line) ⇒ finalize CDR Slide 6
 -  • Work out final design of LV+HV system (grounding scheme, PS already purchased) Slide 7
 -  • Continue analysis of mCBM data Slide 13
 -  • Reviews: Slide 10
- LV+HV EDR (10/21), Module-FOS + PRR-follow-up (12/21), Inner modules EDR (12/21),
Support + mainframe EDR (12/21), SPADIC PRR + FEB CDR (12/21), Radiator EDR (12/21)

C. Blume, TRD status; CBM
Technical Board Meeting 7.09.2021

Open issues/risks

-  • Electronics noise level with next SPADIC generations
-  • Physics performance studies with TRD-2D (inclusion of TRD-2D in tracking) Slide 12
-  • Funding: only one gas line currently funded, secure available funds for electronics (BMBF 19-21)



Construction

TRD1D_type_5 - pre-production

P. Kaehler, Start of TRD module production; 2021 CBM Progress Report, 2022

- 35 modules are planned to be produced, 32 + 3 spare
- 5 to be finalized during the 2nd half of 2022
- delay of pad-plane acquisition, modification of the acquisition chain (direct)

Technological steps

1. backpanel carrier
2. backpanel complete (read-out cathode)
3. entrance window frame
4. entrance window complete (drift)
5. wire electrodes layers (anode, cathode)
6. chamber closing





Figure 2: Padplane for the segmented TRD read-out cathode, intrinsically gas-tight connections by 4-layer design.



QA procedures

1. glueing padplane on backpanel carrier
 - planarity better 15 μm , probably even below
2. characterisation of pre-stretched entrance window
 - for characterization w.r.t. to relative detector pressure (Luisa, Felix)
 - good values, given as input for gas system design
3. complete entrance window planarity (prestretched foil+frame) --> full OK for chamber mounting




Construction

TRD2D_type_9 prototype, TDVs, EW optimization




TRD2D type_9 upgrade
TRD1D type_1 from TDR


- technology steps** for chamber assembly are being defined and *Tools Devices and Verifiers* (TDVs) are devised to assure QA during production.
- prototype** all components were prepared and ready (02/22). One TDV is missing (the 1.5 mm wire comb - offer from Uni-Heidelberg)
- production** market investigations are being conducted based on price efficiency estimates during prototype phase (A&K wires, honeycomb)
- optimization** fine tuning of components to improve material budget (FEB) or TR



Sample	Sample
1. 2 x 75 μm Kapton foil + 9 mm honeycomb	4. 2 x 170 μm aluminized carbon fiber + 9 mm honeycomb
2. 2 x 20 μm aluminized Kapton foil + 3 mm Rohacell foam HF71 + 9 mm honeycomb TRD/2D /mCBM entrance window	5. 135 μm carbon fiber + 25 μm aluminized Mylar foil + 9 mm honeycomb + 20 μm aluminized Kapton foil
3. 2 x 0.25 mm aluminized carbon fiber + 9 mm honeycomb	6. 100 μm carbon fiber + 25 μm aluminized Mylar foil + 8 mm Rohacell foam HF71 TRD-ALICE entrance window



GAS system




<https://git.cbm.gsi.de/trd/reports/cdr-gas-system>

- 1. Installation:**
→ first line in Münster. (in progress).
- 2. Objectives :**
→ To characterize measurements,
→ Development of regulation routines.
→ Measure characteristic time of regulation with real pipe lengths / chamber volumes.
- 3. EDR :**
→ Later 2022
- 4. Funds :**
→ First line funded, for the other 4 need to identify resources.


Conceptual Design Review for the TRD gas system

Anton Andronic, Christoph Blume, Daniel Bonaventura, Felix Fidorra and Philipp Kahler
for the TRD group

April 6, 2021




Contents	
1. The CBM TRD	3
2. Gas system layout	5
2.1. TRD geometry: gas line assignment	5
2.2. Detector requirements	5
2.3. Gas option: Ar mode	6
2.4. Functional blocks of the gas system	6
2.5. Installation in CBM	7
2.6. Overview: gas system parameters / technical data	9
3. Detector supply: low-pressure part	10
3.1. Passive flow distribution	10
3.2. Pressure and flow regulation	10
3.3. Feedback to detector design	11
3.4. Pressure protection of the detector system / backup system	11
3.5. Elasticity: time-behaviour of regulation	11
4. Recirculation and purification	12
4.1. Circulation pump	12
4.2. Gas purification	12
5. Xenon recovery plant	14
5.1. Motivation	14
5.2. Xe separation by membranes	14
5.3. Cryogenic Xe recovery	14
6. Development and realisation	15
6.1. Regulation line prototype	15
6.2. Manpower, funding and costs	15
6.3. Day-1 setup	16
7. Operation	17
7.1. Steering and control	17
7.2. Gas analysis	17
7.3. Krypton calibration	17
8. Radiation, detector ageing, general safety aspects	18
8.1. Radiation tolerance	18
8.2. Material choice: avoiding ageing agents	18
8.3. Safety aspects	18
9. TRD-TDR addendum for the Inner Detector Zone	19
References	20
Acknowledgements	21
A. Appendix	22
A.1. Prototype system: component list (pending!)	22
A.2. Study: pressure and flow calculation	23



LV & HV system

HV & LV demonstrator for both TRD(1+2)D @ mCBM



HV. 4 anode lines and 1 drift line were rerouted to the HV unit of TRD1D. Anode slots (0-3) Drift slot 2 (see Fig).


1. full calculation for LV system in place.
2. delayed by concurrent activities
 - production preparation (slide 4)
 - mCBM data taking/analysis (slide)

<https://git.cbm.gsi.de/trd/reports/edr-hv-lv>


**Engineering Design Review
for the TRD HV and LV systems**

Philipp Köhler and Florian Roether
for the TRD group

February 15, 2022



Contents	
1. Introduction: the CBM TRD	3
2. Low voltage system	4
2.1. Front-end electronic power demands	4
2.1.1. Load dependence	5
2.2. Supplies	5
2.3. Connections	6
2.3.1. Cabling	6
2.3.2. Power bus bars	6
2.3.3. Alternative: Aluminium bus bars	8
2.3.4. Material budget	8
2.3.5. Voltage drop, internal sensing and transport losses	8
2.4. DC-DC conversion	8
2.4.1. Noise studies	8
2.5. TRD LV synopsis	9
3. High voltage system	10
3.1. System and requirements	10
3.2. Supplies	10
3.3. Connections	10
3.3.1. Cabling	10
3.3.2. Distribution to detector modules	10
3.3.3. Distribution boards	10
4. Grounding scheme	11
4.1. Ground net topology	11
5. Operation	12
5.1. Control and monitoring	12
5.1.1. LV	12
5.1.2. HV	12
5.2. Radiation levels	12
5.3. Repair procedures	12
5.3.1. LV	12
5.3.2. HV	12
6. Safety aspects	13
6.1. LV and fire safety	13
6.2. HV safety aspects	13
References	14
A. Appendix	15
A.1. Radiation environment	15



FEE : SPADIC

C. Blume, TRD status; CBM Technical Board Meeting 7.09.2021


https://indico.gsi.de/event/13081/contributions/55770/attachments/36880/49242/trd_status_07.09.21.pdf

SPADIC v2.3a, v2.3b


- Both test chips are on FEBs now.
- Expert team at ZITI is evaluating the chips.

SPADIC v2.4

- will be designed/configured according to the results of the evaluation. (e.g. choice of input protections).
- No extra new features




FEE : FASPI/GETS




Mounting the 14 new FASPRO boards on the TRD2D. The operated region was modified wrt planning as follows (see picture, top to the right):

- from 3 → 2 FASPRO columns
- from 6 → 9 FASPRO rows
- similar read-out surface
- more emphasis on low deflection angles (higher multiplicity)
- matching better with ToF acceptance
- easier to mount as the old 4 boards were kept in position


Mounting the corresponding GETS boards. The red cables left floating are the connections to the CROB. Due to topological reasons the allocation GETS → CROB will differ from previous runs which will impact the software mapping !






Milestones 2022

<p>JAN</p>	<p>FEB</p> <p>LV+HV EDR</p> <ul style="list-style-type: none"> → pending → to be arranged soon 	<p>MAR</p>	<p>APR</p> <p>LV+HV PRR</p> <ul style="list-style-type: none"> → pending → EDR merged ?
<p>MAY</p> <p>Radiator EDR</p> <ul style="list-style-type: none"> → to be arranged soon → layer spacing <p>Support</p> <p>+ Mainframe EDR</p> <ul style="list-style-type: none"> → to be arranged soon → layer spacing 	<p>JUN</p> <p>TDR Addendum ECE</p> <ul style="list-style-type: none"> → in preparation → need CBM support 	<p>JUL</p> <p>Gas EDR</p> <ul style="list-style-type: none"> → in preparation <p>Mod_type_9 (inner)</p> <p>start production</p> <ul style="list-style-type: none"> → pending (+1y) 	<p>AUG</p>
<p>SEP</p> <p>Mod_type_9 (inner)</p> <p>EDR</p> <ul style="list-style-type: none"> → tentative (old 09/21) <p>Support</p> <p>+ Mainframe PRR</p> <ul style="list-style-type: none"> → depends on 	<p>OCT</p> <p>Mod_type_5 FOS + PRR</p> <ul style="list-style-type: none"> → follow-up 	<p>NOV</p> <p>SPADIC (v2.4) PRR</p> <ul style="list-style-type: none"> → tentative (old 05/22) <p>FEB CDR</p> <ul style="list-style-type: none"> → tentative (old 05/22) <p>FEB EDR</p> <p>TDR Addendum approval</p> <ul style="list-style-type: none"> → tentative (old 11/21) 	<p>DEC</p>



TRD(2D) track seeding

TRD inner zone low p_T



p & K⁺ with $|y_{CM}| < 0.25$, propagated from STS seeds to last TRD station. Hatched area is a projection of the STS blind spot.

... tracks which attach TRD hits. The hatched area shows a low efficiency!


... tracks which IDEALLY can be reconstructed starting from TRD-2D seeding

THE PROTONS DISTRIBUTION CAN BE REPRODUCED FOR EACH CHARGED PARTICLE WITH PROPER B FIELD SETTINGS

TRD-2D seeding:


- can be done with at least 2 hits
- x-y resolution independent of missing station!

Once a TRD seed is produced we need only few (2) sparse STS hits to estimate p_T



No dedicated list of recommendations from the reviewers so far. A deadline from the collaboration can be asked for June-July


Informal meeting on TRD TDR Addendum 4th May 2022



TRD(2D) track seeding

S. Gorbunov; private communication,

Tracker type	PID	Efficiency (%)
TRD2D (4 hits)	any	92,8
	protons and kaons	93,8
	pions	92,2
	electrons	85,7



Δ_x (residuals) between TRD2D hits and MC points as function of $\varphi = p_x/p_z$.
 $\sigma_x(\varphi) = p0 + p1 * \varphi^2$; $p0$ and $p1$ are expressed in μm

https://git.cbm.gsi.de/computing/cbmroot/-/merge_requests/818

For tracking performance the value of reference is the ration:



$$\text{Pull} = \Delta_x / \sigma_x$$


The distribution of this observable has to be Gauss with mean 0 and sigma 1.





In the figure the pull_x distribution is shown for TRD1D and TRD2D as they are produced by the `CbmTrackerInputQaTrd` task.

The performance can be improved in terms of χ^2 by improving the error parametrization.







Results, mCBM and beyond



The mCBM experiment
at GSI SIS18
March 27, 2022






On mCBM data




A. Bercuci et al.; Steps towards integration of the TRD-2D detection system with the CBM experiment. *CBM PR'21*

A. Bercuci et al.; Global space-time correlation of the local TRD reconstruction within the mCBM environment, *CBM PR'21*



A. Puntke; private communication





On mCBM correlations




Track definition 2xSTS + 2xToF

x (high resolution) direction


y direction



A. Bercuci et al.; Steps towards integration of the TRD-2D detection system with the CBM experiment, CBM PR'21`




Hit-track resolution is only informative. Calibration, alignment, fixes of mCBM data are work in progress.



Other mCBM results

Time-based Simulations


- O-Ni 2 AGeV mbias
- Interaction rate @ 100 kHz:




A. Nan; AFCO poster presentation, Brasov, ROMANIA

Charge Calibrations

TRD2D Charge calibration




Simultaneous charge calibration of all FASP channels through injection of a standard signal (square, amplitude, frequency) on the anode wires.



CBM simulations



PID references for Di-electron analysis



- ▶ Electron efficiencies set to:
 - ▶ RICH PID: 90%
 - ▶ TRD PID: 80%

A. Meyers-Ahrens; TRD likelihood reference spectra update, TRD Weekly 11.05.2022



High hit times




S. Gaessel; TRD hit times, electron/light nuclei input, TRD Weekly 16.02.2022

Hits QA

S.Gorbunov, A.Bercuci; https://git.cbm.gsi.de/computing/cbmroot/-/merge_requests/818







Outlook

P. Kaehler, TRD summary; 38th CBM Collaboration Meeting; 27.09- 1.10 2021

“2024 setup”


- aiming for full setup in 2025 → **2026 (2027)**
- “2024 setup” scrutinised (current funding consent, day-1 scenario)
- funding 2024/2025 open, funding further gas system lines open



Type 5: BMBF 19–21
 Type 3 (partially): BMBF 21–24
 Type 1: Romania → **type 9**


7	7	3	3	3	3	7	7
		3	3	3	3		
7	5	3	3	3	3	5	7
		1	1	1	1		
5	5	1			1	5	5
		1	1	1	1		
7	5	3	3	3	3	5	7
		3	3	3	3		
7	7	3	3	3	3	7	7
		3	3	3	3		

Christoph/Etienne, PWG-DIL 14.05.



Milestones 2023


<p>JAN</p>	<p>FEB</p> <p>Mod_type_5 FAT → end production Mod_type_3 FAT → start production Gas PRR → old (07/22)</p>	<p>MAR</p> <p>Support + Mainframe FAT</p> <p>SPADIC 2.4 FAT FEB(SPADIC) PRR</p>	<p>APR</p> <p>Radiator FAT</p>
<p>MAY</p>	<p>JUN</p> <p>Mod_type_3 FOS (PRR) Mod_type_9 FOS (10)</p> <p>FEB(SPADIC) FOS</p>	<p>JUL</p>	<p>AUG</p>
<p>SEP</p>	<p>OCT</p>	<p>NOV</p> <p>Gas FAT</p>	<p>DEC</p> <p>Mod_type_3 FAT → end production</p> <p>FEB(SPADIC) FAT</p>



BACKUP

TRD - Outer Chambers/modules

Milestone	Date	2019	2020	2021	2022	2023	2024	2025
Outer modules "5"								
Module EDR	10/19	👍						
Module PRR + Start of prod.	10/20		👍				Acceptance on-going	
Modules FOS + PRR follow up	12/21 10/22			👍	👍		Production on-going	
Chambers all built (FAT)	07/22 02/23				👍	👍		
Outer modules "3"								
Start of prod.	05/22 02/23				👍	👍		
FOS (PRR follow-up if needed)	07/22 06/23				👍	👍		
All built (FAT)	12/23						👍	
Outer modules "7"								




TRD - Inner Chambers/Modules

Milestone	Date	2019	2020	2021	2022	2023	2024	2025
Inner modules (chamber + radiator + FEE)								
TDR-Add internal review	02/21			👍				
TDR-Add submission	05/21			👍			ECE 05/2021	
Inner modules "EDR"	09/21 01/22				👍		Moved ☒ 05/22 ? (should be discussed)	
TDR Addendum approval	11/21			👍			ECE 11/2021	
Inner modules PRR	02/22				👍			
Start module production	07/22				👍			
Module FOS (batch of 10)	06/23					👍		
All chambers built	06/24						👍	


TRD – Radiator box, Services, Mechanics

Milestone	Date	2019	2020	2021	2022	2023	2024	2025
Radiator box								
Radiator EDR	05/22				👍	decision on layer spacing needed		
Radiator PRR	07/22				👍			
Radiator FAT	04/23					👍		
Gas system								
Gas CDR	04/21			👍		evaluation ongoing		
Gas EDR	02/22 07/22				👍	👍	more time for preparation. funding?	
Gas PRR	07/22					👍		
Gas FAT	11/23						👍	
LV + HV systems								
LV + HV EDR	02/22				👍	being prepared		
LV + HV PRR	04/22				👍	can EDR and PRR be merged?		
LV + HV FAT	09/22				👍			
Mechanics								
Mainframe CDR	10/20		👍					
Support + Mainframe EDR	05/22				👍	decision on layer spacing needed		
Support + Mainframe PRR	09/22				👍			
Support + Mainframe FAT	03/23					👍		



TRD – ASIC, FEBs


Milestone	Date	2019	2020	2021	2022	2023	2024	2025
SPADIC ASIC + Front-End Boards								
SPADIC 2.2 completed	07/19	👍						
SPADIC 2.3 submission	12/20		👍					
SPADIC 2.4 PRR	05/22				👍	SPADIC 2.3 evaluation on-going, 2.3b just delivered		
SPADIC 2.4 FAT	03/23					👍		
FEB CDR	05/22				👍			
FEB EDR	1/22 11/22					👍		
FEB PRR	03/23					👍		
FEB FOS, 1 st batch sent	06/23						👍	
FEB FAT, all FEBs sent	12/23						👍	



Layer Spacing



- Options (currently under discussion)




Version 1

Layer spacing: **710 mm**

Radiators mounted on MWPCs

Reduced acceptance
(# points on track)

⇒ *PID performance reduced*




Version 2

Layer spacing: **531 cm**

Radiators mounted in support frame

Air gap between radiator and MWPC

Reduced size of radiators
⇒ *Radiator perf. reduced*




Version 3

Layer spacing: **531 cm**

Radiators split into two parts





Air gap between radiator parts

⇒ *Radiator perf. reduced*




Layer Spacing

- Reduced acceptance (version 1)
 - # of points decreases with increasing layer spacing
 - Effect prominent in specific areas of phase space
- Effect on di-electron performance
- dEdx-performance would also be affected




C. Blume, TB Meeting, Sept. 7th 2021



Layer Spacing




- Alternative radiator mounting (version 2 + 3)
 - Air gaps between radiator + MWPC, resp. radiator parts, for mechanical clearance
 - Bulging of foam foil stack requires ~ 40 mm
 - Absorption of TR-photons



- Reduction of radiator performance (up to factor ~ 2)



2 Mio Events, 3 GeV, 90 % e eff



C. Blume, TB Meeting, Sept. 7th 2021

Layer Spacing



- Next steps
 - Apparently no clear preference from physics performance point-of-view
 - Other considerations:
 - Simplicity of design (radiators, support)
 - Ease of maintenance
 - External constraints:
 - Short TRD-setup required by general CBM setup?
 - Encapsulated radiators needed (fire safety)?
 - Have to come to a decision soon
 - Submit design change request

C. Blume, TB Meeting, Sept. 7th 2021

10